

The CM-BN258IR Exterior IR Bullet Camera



Key Features

- High Sensitive 1/3" SONY Super HAD CCD
- Built-in Fixed Lens (f=6mm)
- Normal Resolution : 380 TV Lines
- Min. Illumination : 0.00 Lux
- AWB, AGC
- Weather-proof Housing (IP67)

ITEM	CM-BN258IR	CM-BP258IR
Signal System	NTSC	PAL
Scanning System	2:1 Interlace	
Scanning Frequency (VH)	15.734KHz	15.625KHz
Scanning Frequency (V)	59.94Hz	50Hz
Image Sensor	1/3" SONY Super HAD	
Total Pixels	537H x 505V (270K)	537H x 597V (320K)
Effective Pixels	510H x 492V(250K)	500H x 582V(290K)
Resolution	380 TV Lines	
Video Output	1.0 Vp-p (75 ohm Composite)	
S/N Ratio	More than 48dB (AGC Off)	
Lens	Fixed Lens (f=6.0mm)	
Angle of View	60°	
Min. Illumination	0.00Lux(IR LED On)	
White Balance	Auto	
AGC	Auto	
IR LED & Sensor	IR LED (850nm, 30') 9ea, Sensor 1 ea.	
IR LED Visible Range	Max 10M.	
Input/Output Connector	Power in jack (red), Video out jack (yellow)	
Shutter Speed	1/60 – 1/100,000 sec.	1/50 – 1/100,000 sec.
Power Supply	DC10V ~ 14V (Recommended DC12±0.5V)	
Power Consumption	Less than 200mA, 2.0W(Max)	
Dimension (mm)	68(W) X 83.16(H) X 102(D w/o bracket)	